

GLIDDEN CO

-- GLID-GUARD TANK & STRUCTURAL PRIMER, 5206

=====
Material Safety Data Sheet
=====

NIIN: 01-374-3391
MSDS Num: CBRBC
MSDS NAME: GLID-GUARD TANK & STRUCTURAL PRIMER, 5206
Responsible Party
Name: GLIDDEN CO
Address: 925 EUCLID AVE
City: CLEVELAND OH 44115
Info Phone: 216-344-8207
Emergency Phone Number: 800-545-2643
Proprietary Ind: Y
Published: Y

=====
Contractor Summary
=====

Name: GLIDDEN CO MEMBER OF ICI WORLD PAINTS
Address: 925 EUCLID AVE
Box: 15049
City: CLEVELAND OH 44115
Phone: 216-344-8000
Name: GLIDDEN PAINT, ICI PAINTS NORTH AMERICA
Address: 925 EUCLID AVE
City: CLEVELAND OH 44115
Phone: 800-545-2643/216-344-8207

=====
Item Description Information
=====

Item Name: PRIMER COATING
=====

Ingredients
=====

Name: *** PROPRIETARY ***

=====

Health Hazards Data
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: YES
IARC: YES
OSHA: NO
Effects of Exposure: INHAL:IRRIT OF RESP TRACT. PRLNG INHAL MAY LEAD TO FATG
,
DROW, DIZZ &/OR LT HEAD, HDCH, UNCOORD, NAUS, VOMIT, COUGH, CNS DEPRESS,
RESP PROBS, INTOX, TIGHTNESS OF CHEST, CONFUSN, ANESTH EFT/NARCOS, DFC LTY
IN
BRTHG. SKIN:IRRIT. PRLNG/RPTD CONT CAN CAUSE DERM, DEFAT, SEV IRRIT OR BUR
NS.
MAY BE ABSORBED. (EFTS OF OVEREXP)
Explanation Of Carcinogenicity: SEE "LR" VERSION FOR ADDITIONAL INFORMATION
(FP N).

Signs And Symptoms Of Overexposure: HLTH HAZ:EYE:IRRIT. PRLNG/RPTD CONT CAN CAUSE BLURRED VISION, TEARING, REDNESS, SEV IRRIT, CORNEAL INJURY. INGEST: MAY

CAUSE LUNG INFLAMM & DMG DUE TO ASPIR OF MATL INTO LUNGS, HDCH, NAUS, VOMIT, DIARR , GI DISTURBS, SEV ABDOM PAIN, CNS DEPRESS, ANESTH EFT/NARCOS

MOD TOX. NOTICE:RPTS HAVE ASSOC RPTD & PRLNG (SUPP DATA)

Medical Cond Aggravated By Exposure: INGS CONTAINED IN THESE PRODUCTS HAVE BEEN

REPORTED TO AGGRAVATE PREEXISTING EYE, SKIN, RESPIRATORY & LUNG DISORDERS, ASTHMA-LIKE CONDITIONS, CARDIAC ABNORMALITIES, KIDNEY DISORDERS & LIVER DISORDERS.

First Aid: INHAL:REMOVE TO FRESH AIR. RESTORE & SUPPORT CONTINUED BRTHG.

GET EMER MED ATTN. HAVE TRAINED PERS GIVE OXYG IF NEC. GET MED HELP FOR ANY

BRTHG DFCLTY. SKIN:WASH OFF QUICKLY W/PLENTY OF WATER, THEN SO AP & WATER; REMOVE CONTAM CLTHG. WASH CONTAM CLTHG BEFORE REUSE. EYES:FLUSH IMM

ED W/LG AMTS OF WATER, ESP UNDER LIDS, FOR AT LST 15 MINS. IF IRRIT/OTHER EFTS PERSIST, OBTAIN MED TREATMENT. (SUPP DATA)

=====
Handling and Disposal
=====

Spill Release Procedures: COMPLY W/ALL APPLICABLE HEALTH & ENVIRONMENTAL REGULATIONS. ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. SPILLS MAY BE

COLLECTED W/NONCOMBUST ABSORB MATLS. USE NON-SPARKING TOOLS. EVACUATE ALL UN

NNEC PERS. VACUUM CLEAN SPILLAGE. TOXIC TO FISH.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS (FP N). DISPOSE I/A/W ALL APPLICABLE REGULATIONS. AVOID DISCHARGE

TO NATURAL WATERS.

Handling And Storage Precautions: STORE <100F. KEEP AWAY FROM HEAT, SPKS & OPEN FLAME. USE ONLY W/ADEQ VENT. KEEP OUT OF REACH OF CHILDREN. AVOID CONT W/SKIN & EYES, & BRTHG OF VAPS.

Other Precautions: DO NOT TAKE INTERNALLY. KEEP CONTAINERS TIGHTLY CLOSED & UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES. GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION OF STATIC CHARGE.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: >108F,>42C

Lower Limits: SEE INGS

Extinguishing Media: DRY CHEMICAL OR FOAM.

Fire Fighting Procedures: USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N). WATER MAY BE USED TO COOL & PROTECT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard: CLSD CNTNRS MAY EXPLODE WHEN EXPOS TO EXTREME HEAT/FIRE. VAPS MAY IGNITE EXPLOSIVELY AT AMBIENT TEMPS. VAPS ARE HVR/AIR & MAY TRAVEL LONG DISTS TO A (SUPP DATA)

=====
Control Measures
=====

Respiratory Protection: CONTROL ENVIRON CONCS BELOW APPLIC STDS. WHERE RESP
PROT IS REQD, USE ONLY NIOSH APPRVD RESPS I/A/W OSHA STD 29 CFR 1910.134.
AVOID CNDTNS WHICH RSLT IN FORM OF INHALABLE PARTICLES SUCH AS SPRAYING/AB
RADING (SANDING) PAINTED

Ventilation: PROVIDE DILUTION VENT/LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPO
RS.

USE EXPLO-PROOF EQUIP. USE NON-SPARKING EQUIPMENT.

Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).

Other Protective Equipment: EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANS
I

DESIGN CRITERIA (FP N).

Work Hygienic Practices: WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY
BEFORE EATING OR SMOKING.

Supplemental Safety and Health: NOTE:USERS OF "L" VERSION SHOULD CONSULT "LR
"

VERSION FOR ADDNL INFO (FP N). EXPLO HAZ:SOURCE OF IGNIT & FLASH BACK.
MAY DECOMPOSE UNDER FIRE CNDTNS EMITTING IRRIT &/OR TOX GASES. MATLS TO
AVOID:POTAS SIUM, WATER. FIRST AID PROC:INGEST: OBTAIN MED TREATMENT IMMED

EFTS OF OVEREXP:OCCUP OVEREXP TO SOLVS W/PERM

=====
Physical/Chemical Properties
=====

B.P. Text: >300F,>149C

Vapor Pres: SEE INGS

Spec Gravity: 1.39 (FP N)

Appearance and Odor: NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume: 48.3
=====

Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: ELEVATED TEMPERATURES, CONTACT W/OXIDIZING AGE
NT.

Materials To Avoid: OXIDIZERS, ACIDS, BASES, ISOCYANATES, AMINES, PYRIDINES,
ALUMINUM, ZINC, MAGNESIUM, MINERAL ACIDS, SODIUM, (SUPP DATA)

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT
=====

Toxicological Information
=====

Ecological Information
=====

MSDS Transport Information
=====

Regulatory Information
=====

Other Information
=====

HAZCOM Label

=====
MSDS NAME: GLID-GUARD TANK & STRUCTURAL PRIMER, 5206
Company: GLIDDEN CO MEMBER OF ICI WORLD PAINTS
Street: 925 EUCLID AVE
PO Box: 15049
City: CLEVELAND OH
Zipcode: 44115
Health Emergency Phone: 800-545-2643
Label Required IND: Y
Date Of Label Review: 07/25/1996
Status Code: C
Label Date: 07/25/1996
Origination Code: G
Chronic Hazard IND: Y
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: WARNING
Respiratory Protection IND: YES
Health Hazare: Moderate
Contact Hazard: Slight
Fire Hazard: Moderate
Reactivity Hazard: None
Hazard And Precautions: COMBUSTIBLE. ACUTE:INHAL:IRRIT OF RESP TRACT. PRLNG
INHAL MAY LEAD TO FATIGUE, DROW, DIZZ &/OR LT HEAD, HDCH, UNCOORD, NAUS,
VOMIT, COUGH, CENTRAL NERVOUS SYSTEM DEPRESS, RESP PROBLEMS, INTOX, TIGHTN
E
SS OF CHEST, CONFUSION, ANESTHETIC EFT/NARCOSIS, DIFFICULTY IN BRTHG.
SKIN:IRRIT. MAY BE ABSORBED. EYE:IRRIT. INGEST:ASPIR HAZ. CENTRAL NERVOUS
SYSTEM DEPRESS, SEVERE ABDOM PAIN, MODERATELY TOXIC. CHR ONIC:CANCER HAZAR
D.
CONTAINS MATL WHICH IS LISTED AS AN ANIMAL LUNG CARCINOGEN (FP N). MAY CAU
SE
SILICOSIS, PERM BRAIN/NERV SYS DMG. SKIN:PRLNG/RPTD CONT CAN CAUSE DERM,
DEFAT, SEVERE IRRIT/BURNS. EYE S:BLURRED VISION, SEVERE IRRIT, CORNEAL
DAMAGE.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense
.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use
or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the Unit
ed
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of t
he
United States of America should seek competent professional advice to veri
fy
and assume responsibility for the suitability of this information to their
particular situation regardless of similarity to a corresponding Departmen
t
of Defense or other government situation.

*** END OF RECORD ***