

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Toluene

Product Number : 648566
Brand : Sigma-Aldrich

Supplier : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052
Emergency Phone # (For both supplier and manufacturer) : (314) 776-6555

Preparation Information : Sigma-Aldrich Corporation
Product Safety - Americas Region
1-800-521-8956

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant, Teratogen, Reproductive hazard

Target Organs

Bladder, Liver, Kidney, Brain.

GHS Classification

Flammable liquids (Category 2)
Acute toxicity, Inhalation (Category 4)
Skin irritation (Category 2)
Eye irritation (Category 2A)
Reproductive toxicity (Category 2)
Specific target organ toxicity - single exposure (Category 2)
Specific target organ toxicity - single exposure (Category 3)
Aspiration hazard (Category 1)
Acute aquatic toxicity (Category 2)

GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H371 May cause damage to organs.

H401 Toxic to aquatic life.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P281 Use personal protective equipment as required.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331 Do NOT induce vomiting.

HMIS Classification

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical hazards: 0

NFPA Rating

Health hazard: 2
Fire: 3
Reactivity Hazard: 0

Potential Health Effects

Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Skin May be harmful if absorbed through skin. Causes skin irritation.
Eyes Causes eye irritation.
Ingestion May be harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C₇H₈
Molecular Weight : 92.14 g/mol

Component	Concentration
Toluene	
CAS-No. 108-88-3	-
EC-No. 203-625-9	
Index-No. 601-021-00-3	

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

7. HANDLING AND STORAGE**Precautions for safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Basis
Toluene	108-88-3	TWA	100 ppm 375 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	150 ppm 560 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	200 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z2
Remarks	Z37.12-1967			
		CEIL	300 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z2
	Z37.12-1967			
		Peak	500 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z2
	Z37.12-1967			
		TWA	20 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Visual impairment Female reproductive Pregnancy loss 2010 Adoption Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human			

	carcinogen			
		TWA	100 ppm 375 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	150 ppm 560 mg/m3	USA. NIOSH Recommended Exposure Limits

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form liquid

Colour colourless

Safety data

pH no data available

Melting point/freezing point Melting point/range: -93 °C (-135 °F)

Boiling point 110 - 111 °C (230 - 232 °F)

Flash point 4.0 °C (39.2 °F) - closed cup

Ignition temperature	535 °C (995 °F)
Auto-ignition temperature	535.0 °C (995.0 °F)
Lower explosion limit	1.2 %(V)
Upper explosion limit	7 %(V)
Vapour pressure	29.1 hPa (21.8 mmHg) at 20.0 °C (68.0 °F)
Density	0.865 g/mL at 25 °C (77 °F)
Water solubility	no data available
Partition coefficient: n-octanol/water	no data available
Relative vapour density	no data available
Odour	no data available
Odour Threshold	no data available
Evaporation rate	no data available

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Materials to avoid

Strong oxidizing agents

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

LD50 Oral - rat - > 5,580 mg/kg

Inhalation LC50

LC50 Inhalation - rat - 4 h - 12,500 - 28,800 mg/m³

Dermal LD50

LD50 Dermal - rabbit - 12,196 mg/kg

Other information on acute toxicity

no data available

Skin corrosion/irritation

Skin - rabbit - Skin irritation - 24 h

Serious eye damage/eye irritation

no data available

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

Genotoxicity in vitro - rat - Liver

DNA damage

Carcinogenicity

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Toluene)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Reproductive toxicity - rat - Inhalation

Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count).

Experiments have shown reproductive toxicity effects in male and female laboratory animals.

Teratogenicity

Developmental Toxicity - rat - Oral

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Damage to fetus possible

Suspected human reproductive toxicant

Specific target organ toxicity - single exposure (Globally Harmonized System)

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

Aspiration hazard

no data available

Potential health effects

Inhalation	May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Ingestion	May be harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.
Skin	May be harmful if absorbed through skin. Causes skin irritation.
Eyes	Causes eye irritation.

Signs and Symptoms of Exposure

Lung irritation, chest pain, pulmonary edema, Inhalation studies on toluene have demonstrated the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals.

Synergistic effects

no data available

Additional Information

RTECS: XS5250000

12. ECOLOGICAL INFORMATION

Toxicity

Toxicity to fish	LC50 - Lepomis macrochirus (Bluegill) - 74.00 - 340.00 mg/l - 96 h
	LC50 - Oncorhynchus mykiss (rainbow trout) - 7.63 mg/l - 96 h
	NOEC - Pimephales promelas (fathead minnow) - 5.44 mg/l - 7 d
	LOEC - Pimephales promelas (fathead minnow) - 8.04 mg/l - 7 d
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 8.00 mg/l - 24 h
	Immobilization EC50 - Daphnia magna (Water flea) - 6 mg/l - 48 h

Toxicity to algae EC50 - Chlorella vulgaris (Fresh water algae) - 245.00 mg/l - 24 h
EC50 - Pseudokirchneriella subcapitata (green algae) - 10.00 mg/l - 24 h

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Mobility in soil

no data available

PBT and vPvB assessment

no data available

Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1294 Class: 3 Packing group: II

Proper shipping name: Toluene

Reportable Quantity (RQ): 1000 lbs

Marine pollutant: No

Poison Inhalation Hazard: No

IMDG

UN number: 1294 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: TOLUENE

Marine pollutant: No

IATA

UN number: 1294 Class: 3 Packing group: II

Proper shipping name: Toluene

15. REGULATORY INFORMATION

OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant, Teratogen, Reproductive hazard

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Toluene	108-88-3	2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Toluene	CAS-No. 108-88-3	Revision Date 2007-07-01
Pennsylvania Right To Know Components		
Toluene	CAS-No. 108-88-3	Revision Date 2007-07-01
New Jersey Right To Know Components		
Toluene	CAS-No. 108-88-3	Revision Date 2007-07-01
California Prop. 65 Components		
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	CAS-No. 108-88-3	Revision Date 2009-02-01
Toluene		

16. OTHER INFORMATION

Further information

Copyright 2013 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.
